

## a new era in **high-productivity** qPCR

Applied Biosystems® ViiA™ 7 Real-Time PCR System



#### a new era in high-productivity qPCR

The ViiA<sup>™</sup> 7 Real-Time PCR System delivers the proven reliability, sensitivity, and accuracy you expect from Applied Biosystems, with new features designed for high-productivity qPCR. Building on the gold-standard design elements of six generations of real-time PCR systems, the ViiA<sup>™</sup> 7 Real-Time PCR System makes it easier to get the high-quality results you need.

- Accomplish more, faster. Run hundreds of qPCR reactions simultaneously on the ViiA<sup>™</sup> 7
   System with TaqMan<sup>®</sup> Array Micro Fluidic Cards. The fully integrated workflow speeds your time-to-results.
- Skip the learning curve. The ViiA™ 7 System's intuitive software, easy touch screen setup, automation integration, and effortless block exchange are designed to let you get started right away.
- Get results you can trust: well to well, run to run, and instrument to instrument.

  Enhanced fluorescence detection with the OptiFlex™ System offers six excitation and six

  emission filters for more multiplexing flexibility, and higher resolution for more accurate data.
- **Get the flexibility you need.** Easily interchangeable thermal cycling block formats let you select the format that's right for your project. You can choose from standard or Fast 96- and 384-well formats, as well as a novel 384-well TaqMan® Array block.

#### ViiA™ 7 [vee-uh sev-uhn]

#### - high-productivity qPCR instrument


1. A new, 7th-generation real-time PCR system that paves the way for high-productivity qPCR through flexibility, performance, integrated TaqMan® Assay content, and the most advanced set of features available.



#### productivity. integration. performance.

The ViiA™ 7 Real-Time PCR System combines all of the qPCR features you want in a single high-performance instrument, so that you can optimize your research productivity. With a simplified workflow, intuitive software, touch screen interface, and one-button protocols for error minimization, the ViiA™ 7 System offers exceptional reproducibility with minimal well-to-well and instrument-to-instrument variation. Full compatibility with any standard or fast-cycling 384- or 96-well plates and TaqMan® Array Micro Fluidic Cards and Reagents makes high-productivity real-time PCR accessible to labs of any size.







TaqMan® Array Micro Fluidic Card. Streamlines reaction setup, does not require liquid-handling robotics, and provides standardization when screening selected panels of genes.

#### Productivity...

#### High-performance features for maximum productivity

Ideal for performing medium- to highthroughput real-time PCR, the ViiA™ 7 System enhances your lab's productivity.

- Quick block changes: Front access makes it easy to change thermal cycling block formats without having to move attached peripherals such as robots or computers.
- Easy touch screen interface: Instrument touch screen provides one-touch protocols for fast and easy assay setup for a broad range of applications.
- Automation compatibility: Integrated with the Applied Biosystems® Twister® II Robot, the ViiA™ 7 System will allow you to maximize productivity for automated environments.
- Peace of mind: Data recovery capability for 100+ runs.

#### Integration...

#### Fully compatible with TaqMan® Array Micro Fluidic Cards

Applied Biosystems® TaqMan® Assays are the gold standard in qPCR analysis, providing high sensitivity, high specificity, and a broad dynamic range.


- TaqMan® Array-ready: Hundreds of customizable and predefined TaqMan® Array Micro Fluidic Cards are available, containing preloaded TaqMan® Gene Expression or MicroRNA Assays in an easy-to-use format. You can analyze 1–8 samples in parallel using your choice of 12–384 TaqMan® Assays.
- 384-well throughput without robotics: With TaqMan® Array Micro Fluidic Cards, there's no need for liquid-handling robotics or complex pipetting to load; simply add your sample and master mix and run on the ViiA™ 7 System.
- Compatible with the full range of TaqMan®
   Assays: The ViiA™ 7 System is optimized
   to enable clear, clean data for all TaqMan®
   Assays, including MicroRNA Assays, Protein
   Assays, Long Non-coding RNA Assays, and
   Pri-miRNA Assays.

#### Performance...

#### New OptiFlex<sup>™</sup> System for unsurpassed accuracy

The ViiA™ 7 System features the new OptiFlex™ System, which provides enhanced fluorescence detection enabling accurate and sensitive data analysis.

- Better accuracy: High-resolution detection system for more accurate reads with TaqMan® Array Micro Fluidic Cards, 384-well plates, and 96-well plates.
- Maximum multiplexing: Six decoupled excitation and emission filter channels for the greatest number of dye combinations and maximum multiplexing capabilities.
- Flexible data collection: Multiple ramp method detection formats provide more flexibility for collecting data during a ramp stage.
- **Precise quantification:** Detect changes as small as 1.5-fold in target quantities in singleplex reactions.



**Real-time reproducibility.** This plot shows results from amplification of 18S target DNA in 10-fold dilutions starting at 25,000 copies, using the 384-well block. The data show highly reproducible results over 9 logs of input template amount, illustrating the broad linear dynamic range of the system.



The ViiA" 7 System is fully integrated with the Applied Biosystems° Twister° II Robot to enable high-productivity qPCR in automated environments.

#### ViiA<sup>™</sup> 7 Software

#### Intuitive, easy-to-use software for maximum productivity

#### Intuitive interface and innovative design

- User-friendly: Easily identifiable icons guide you through the workflow seamlessly to set up runs and analyze experiments. The graphical interface makes it easy to edit the PCR thermal cycling conditions.
- The ViiA<sup>™</sup> 7 remembers your favorites: With the new ReadiApp<sup>™</sup> feature, you can quickly select default protocols for standard applications.

#### Convenient walk-away operation

Enjoy the freedom of operating the Vii $A^{\text{\tiny{M}}}$  7 System from any networked computer.

- Full remote control of up to four instruments: With the ViiA™ 7
   Software Instrument Console, you can review run statistics and remotely control up to four instruments or experiments in real time from your desktop computer. You can also receive email notifications to keep you informed of run and instrument status when you are not in the lab.
- Status monitoring of up to 15 instruments: Up to 15 instruments can be networked for monitoring basic instrument status, so that you always know which instruments are in use and which are available for the next experiment.

#### Expandable software architecture

Optional add-ons are available to upgrade features to existing software.

- 21 CFR Part 11 compliance: The optional SAE module assists with Security, Auditing, and Electronic signature of records for full data traceability.
- Enhanced high-resolution melt (HRM): Using the built-in MeltDoctor™ protocols and calibrations, you can spend less time optimizing the run and more time customizing your results. Define the number of variants you want to see by quickly changing analysis settings.


#### Improved data analysis

The ViiA<sup>™</sup> 7 Software offers innovative approaches to analyze your data.


- Easy management of large data sets: The embedded gene expression (RQ) study application is designed to analyze 100+ runs, while heat maps and scatter plots provide quick checks on data quality.
- Real-time control for genotyping cluster analysis: In genotyping experiments, you can optimize your genotyping run times using a real-time PCR progress monitor to determine the ideal cycle for cluster analysis.

#### Fully compatible with high-throughput environments

- High-throughput experiment setup: Create multiple experiment files simultaneously with the push of a single button. You can import your plate setup files from other Applied Biosystems® real-time systems to facilitate easy experiment setup.
- Easy, automated data export: Set up experiment templates with predefined export preferences and have the ViiA™ 7 Software autoexport to your desired file directory.
- Open API: Open application program interfaces (API) allow integration with third-party systems such as LIMS (laboratory integration management systems) or custom automated platforms.



Allelic discrimination plot with traces using real-time PCR data. Cluster plot of 94 gDNA samples and 2 no-template controls (NTCs) genotyped using TaqMan $^\circ$  SNP Genotyping Assay C\_245448\_10 with both PCR and allelic discrimination performed on the Applied Biosystems $^\circ$  ViiA $^m$ 7 Real-Time PCR System. The novel use of real-time PCR data to plot SNP cluster progress aids in calling ambiguous samples and reducing run times by displaying the optimal number of cycles necessary for maximum cluster separation.



Additional analysis plots are available for quality control. For example, heat maps are available to assess the correlation between samples in gene expression experiments.



With the ViiA™ 7 System, up to four instruments can be remotely controlled and precisely monitored in real time. You can even review detailed run statistics and other vital information remotely and receive status notifications by email. Up to 15 instruments can be networked to provide basic instrument status information from any networked computer.



Intuitive interface and innovative design. Thanks to an intuitive interface and innovative design, with ViiA  $^{\text{m}}$  7 Software you can start a run in less than five clicks with the QuickStart feature, access optimized application protocols using the ReadiApp  $^{\text{m}}$  feature, and create studies directly from the software home screen.



## the complete qPCR solution to advance your research

Our mission is to continually support your path to discovery. The ViiA™ 7 Real-Time PCR System embodies our commitment to providing everything you need for easier, more productive qPCR experiments as part of a complete solution from sample to results. With full integration, everything works together—instruments, software, chemistries, and ready-to-use assays—to enable the consistent, reliable results you need to advance your research.



In addition to instrumentation, software, and consumables, the ViiA™ 7 System includes:

- Professional installation
- Worldwide application and technical support

For more information about the ViiA<sup>™</sup> 7 Real-Time PCR System or any of our qPCR products, contact your Applied Biosystems representative or visit www.appliedbiosystems.com/viia7

## Non-coding RNA

#### Real-Time PCR Reagents

High-quality reagents for sensitive, reliable, and reproducible real-time PCR.

## GENE EXPRESSION TaqMan® Assays

A comprehensive selection of predesigned assays for quantitative gene expression analysis utilizing gold standard TaqMan® Assay chemistry for exceptional sensitivity and specificity, and a broad dynamic range.

# Non-coding RNA

## COPY NUMBER VARIATION SERVICE AND SUPPORT

Our complete qPCR product line is backed by our outstanding worldwide technical support and service programs.

SNP Genotyping

## ViiA™ 7 Real-Time PCR System

## nicroRNA

#### TaqMan® Arrays

Gold standard TaqMan® Assays in easy-to-use micro fluidic card format for high-throughput applications such as drug discovery, disease research, and pathway analysis.



## Sample Prep

Specialized tools for the isolation of highquality nucleic acids for a variety of downstream applications.

### Your Complete Solution for High Productivity qPCR

GENE ESPRESSIONED

Specialized tools for the isolation of highquality nucleic acids for a variety of down



| Block change design         Block change from front of instrument in less than 1 min; no secondary tools required           Temperature uniformity         ±0.5°C, within 30 sec of reaching temperature set point           Run time         -35 min for 384-well, -30 min for 0.2 mL 96-well and 0.1 mL Fast 96-well (using Applied Biosystems* Fast Master Mix)           Demonstrated sensitivity         Down to 1 copy           Opported applications         Standard curve, Comparative Cr, Genotyping, Presence/Absence, HRM, Melt curve           Resolution         Detect changes as little as 1.5-fold in target quantities in singleplex reactions           Supported blocks and volume         56-well fast (10-30 µL reactions) 384-well (5-20 µL reactions) 204-gendic Cards (-1 µL reactions)           12 FFR p11 enablement         Security and auditing features for instrument data           Power         100-240 V, -50/60 Hz           Automation         Includes plate-loading arm w/ barcode (sales, service, and support provided by Life Technologies)           Remote notification         Emails user when run is started, stopped, or aborted           Dia export format         Emails user when run is started, stopped, or aborted           Dia mension (Wx Dx H)         53.5 m(21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)           Weight         6.6 kg   184 b)   | Specifications                   |  |
|--|----------------------------------|--|
| Run time         ~35 min for 384-well, ~30 min for 0.2 mL 96-well and 0.1 mL Fast 96-well (using Applied Biosystems® Fast Master Mix)           Demonstrated sensitivity         Down to 1 copy           Dynamic range         Up to 9 logs of linear dynamic range           Supported applications         Standard curve, Comparative Cr., Genotyping, Presence/Absence, HRM, Melt curve           Resolution         Detect changes as little as 1.5-fold in target quantities in singleplex reaction           Supported blocks and volume         96-well standard [10-100 µL reactions] 96-well Fast [10-30 µL reactions] 384-well [5-20 µL reactions] 120 µL reac   | Block change design              | Block change from front of instrument in less than 1 min; no secondary tools required                                |
| Demonstrated sensitivity         Down to 1 copy           Dynamic range         Up to 9 logs of linear dynamic range           Supported applications         Standard curve, Comparative C <sub>n</sub> , Genotyping, Presence/Absence, HRM, Melt curve           Resolution         Detect changes as little as 1.5-fold in target quantities in singleplex reaction           Supported blocks and volume         96-well standard [10-100 μL reactions] 96-well Fast [10-30 μL reactions] 384-well [15-20 μL reactions] 17-30 μL reactio | Temperature uniformity           | ±0.5°C, within 30 sec of reaching temperature set point  |
| Dynamic range         Up to 9 logs of linear dynamic range           Supported applications         Standard curve, Comparative C <sub>n</sub> , Genotyping, Presence/Absence, HRM, Melt curve           Resolution         Detect changes as little as 1.5-fold in target quantities in singleplex reaction           Supported blocks and volume         96-well standard [10-100 μL reactions] γ6-well Fast [10-30 μL reactions]           Excitation/detection wavelengths         6 excitation [450-670 nm] γ6-wince Fluidic Cards [-1 μL reactions]           21 CFR p11 enablement         Security and auditing features for instrument data           Power         100-240 V, -50/60 Hz           Automation         Includes plate-loading arm w/ barcode [sales, service, and support provided by Life Technologies]           Remote monitoring         Ability to monitor 15 instruments at a time; optional Smart Monitoring Service for remote instrument diagnostic monitoring by Life Technologies           Remote notification         Emails user when run is started, stopped, or aborted           Data export format         Fully configurable by user           Dimension (W x D x H)         53.3 cm [21 in] x 63.5 cm [25 in] x 64.5 cm [25.4 in]  | Run time                         | ~35 min for 384-well, ~30 min for 0.2 mL 96-well and 0.1 mL Fast 96-well (using Applied Biosystems® Fast Master Mix) |
| Supported applications         Standard curve, Comparative C₁, Genotyping, Presence/Absence, HRM, Melt curve           Resolution         Detect changes as little as 1.5-fold in target quantities in singleplex reaction           Supported blocks and volume         96-well standard [10-100 μL reactions] γ6-well Fast [10-30 μL reactions] 384-well [5-20 μL reactions] 17aqMan* Array Micro Fluidic Cards [-1 μL reactions]           Excitation/detection wavelengths         c excitation [450-670 nm] 6 emission [500-720 nm]           21 CFR p11 enablement         Security and auditing features for instrument data           Power         100-240 V, -50/60 Hz           Automation         Includes plate-loading arm w/ barcode (sales, service, and support provided by Life Technologies)           Remote monitoring         Ability to monitor 15 instruments at a time; optional Smart Monitoring Service for remote instrument diagnostic monitoring by Life Technologies           Remote notification         Emails user when run is started, stopped, or aborted           Data export format         Fully configurable by user           Dimension (W x D x H)         53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)   | Demonstrated sensitivity         | Down to 1 copy   |
| ResolutionDetect changes as little as 1.5-fold in target quantities in singleplex reactionSupported blocks and volume%6-well standard (10–100 μL reactions) 96-well Fast (10–30 μL reactions) 384-well (5–20 μL reactions) 17aqMan* Array Micro Fluidic Cards (-1 μL reactions) 17aqMan* Array Micro Fluidic Cards (-1 μL reactions)Excitation/detection wavelengths6 excitation (450–670 nm) 6 emission (500–720 nm)21 CFR p11 enablementSecurity and auditing features for instrument dataPower100–240 V, -50/60 HzAutomationIncludes plate-loading arm w/ barcode (sales, service, and support provided by Life Technologies)Remote monitoringAbility to monitor 15 instruments at a time; optional Smart Monitoring Service for remote instrument diagnostic monitoring by Life TechnologiesRemote notificationEmails user when run is started, stopped, or abortedData export formatFully configurable by userDimension (W x D x H)53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)  | Dynamic range                    | Up to 9 logs of linear dynamic range   |
| Supported blocks and volume96-well standard (10-100 μL reactions)<br>96-well Fast (10-30 μL reactions)<br>384-well (5-20 μL reactions)<br>TaqMan* Array Micro Fluidic Cards (-1 μL reactions)Excitation/detection wavelengths6 excitation (450-670 nm)<br>6 emission (500-720 nm)21 CFR p11 enablementSecurity and auditing features for instrument dataPower100-240 V, ~50/60 HzAutomationIncludes plate-loading arm w/ barcode (sales, service, and support provided by Life Technologies)Remote monitoringAbility to monitor 15 instruments at a time; optional Smart Monitoring Service for remote instrument diagnostic monitoring by<br>Life TechnologiesRemote notificationEmails user when run is started, stopped, or abortedData export formatFully configurable by userDimension (W x D x H)53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)   | Supported applications           | Standard curve, Comparative C <sub>t</sub> , Genotyping, Presence/Absence, HRM, Melt curve                           |
| 96-well Fast (10–30 μL reactions) 384-well (5–20 μL reactions) TaqMan* Array Micro Fluidic Cards (-1 μL reactions)  Excitation/detection wavelengths 6 excitation (450–670 nm) 6 emission (500–720 nm) 21 CFR p11 enablement Security and auditing features for instrument data  Power 100–240 V, -50/60 Hz  Automation Includes plate-loading arm w/ barcode (sales, service, and support provided by Life Technologies)  Remote monitoring Ability to monitor 15 instruments at a time; optional Smart Monitoring Service for remote instrument diagnostic monitoring by Life Technologies  Remote notification Emails user when run is started, stopped, or aborted  Data export format Dimension (W x D x H) 53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)   | Resolution                       | Detect changes as little as 1.5-fold in target quantities in singleplex reaction                                     |
| 21 CFR p11 enablement Security and auditing features for instrument data  Power 100–240 V, ~50/60 Hz  Automation Includes plate-loading arm w/ barcode (sales, service, and support provided by Life Technologies)  Remote monitoring Ability to monitor 15 instruments at a time; optional Smart Monitoring Service for remote instrument diagnostic monitoring by Life Technologies  Remote notification Emails user when run is started, stopped, or aborted  Data export format Fully configurable by user  Dimension (W x D x H) 53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)  | Supported blocks and volume      | 96-well Fast (10–30 µL reactions)<br>384-well (5–20 µL reactions)  |
| Power 100-240 V, ~50/60 Hz  Automation Includes plate-loading arm w/ barcode (sales, service, and support provided by Life Technologies)  Remote monitoring Ability to monitor 15 instruments at a time; optional Smart Monitoring Service for remote instrument diagnostic monitoring by Life Technologies  Remote notification Emails user when run is started, stopped, or aborted  Data export format Fully configurable by user  Dimension (W x D x H) 53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)  | Excitation/detection wavelengths | ,  |
| Automation Includes plate-loading arm w/ barcode (sales, service, and support provided by Life Technologies)  Remote monitoring Ability to monitor 15 instruments at a time; optional Smart Monitoring Service for remote instrument diagnostic monitoring by Life Technologies  Remote notification Emails user when run is started, stopped, or aborted  Data export format Fully configurable by user  Dimension (W x D x H) 53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)  | 21 CFR p11 enablement            | Security and auditing features for instrument data   |
| Remote monitoring Life Technologies  Remote notification Emails user when run is started, stopped, or aborted  Data export format Fully configurable by user  Dimension (W x D x H) 53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)  | Power                            | 100–240 V, ~50/60 Hz   |
| Remote notificationEmails user when run is started, stopped, or abortedData export formatFully configurable by userDimension (W x D x H)53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)  | Automation                       | Includes plate-loading arm w/ barcode (sales, service, and support provided by Life Technologies)                    |
| Data export format  Fully configurable by user  53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)  | Remote monitoring                |  |
| Dimension (W x D x H) 53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)  | Remote notification              | Emails user when run is started, stopped, or aborted   |
|  | Data export format               | Fully configurable by user   |
| <b>Weight</b> 66.9 kg [148 lb]   | Dimension (W x D x H)            | 53.3 cm (21 in) x 63.5 cm (25 in) x 64.5 cm (25.4 in)  |
|  | Weight                           | 66.9 kg (148 lb)   |

#### **Ordering information**

| ordering into mation  |             |
|---|-------------|
| Instrument systems  | P/N         |
| Applied Biosystems® ViiA™ 7 Real-Time PCR System with 384-Well Block      | 4453536     |
| Applied Biosystems® ViiA™ 7 Real-Time PCR System with TaqMan® Array Block | 4453537     |
| Applied Biosystems® ViiA™ 7 Real-Time PCR System with 96-Well Fast Block  | 4453535     |
| Applied Biosystems® ViiA™ 7 Real-Time PCR System with 96-Well Block       | 4453534     |
| Accessories   |             |
| ViiA <sup>™</sup> 7 System Automation Accessory Robot (100–240 V)         | 4453551     |
| 384-Well Block Upgrade Kit  | 4453545     |
| TaqMan® Array Upgrade Kit   | 4453546     |
| 96-Well Fast Block Upgrade Kit  | 4453544     |
| 96-Well Block Upgrade Kit   | 4453543     |
| Services  |             |
| 1-Year Extended Warranty, ViiA** 7 System                                 | ZG61SCVIIA7 |
| Software add-ons  |             |
| ViiA <sup>™</sup> 7 Software HRM Module                                   | 4453724     |
| ViiA <sup>™</sup> 7 Software 21 CFR Part 11 Module                        | 4453723     |
|   |             |

 $\label{life-products} \mbox{Life-Technologies offers a breadth of products} \mbox{ } \mbox{DNA } \mbox{ } \mbox{ } \mbox{PROTEIN } \mbox{ } \mbox{CELL-CULTURE } \mbox{ } \mbox{INSTRUMENTS}$ 

For Research Use Only. Not intended for any animal or human therapeutic or diagnostic use.

© 2011 Life Technologies Corporation. All rights reserved. The trademarks mentioned herein are the property of Life Technologies Corporation or their respective owners. TaqMan is a registered trademark of Roche Molecular Systems, Inc. **C016738 0211** 

